



Fas LITE LIF

WWW.FAS.IT





MAIN FEATURES

Enlarged capacity

Delivery bin and delivery door with enlarged dimensions to ensure the withdrawl of bulky products compared to the normal standard

10" Interface tablet

Interface enduser touchscreen customizeable with logos, videos Programming iconographic easy and fast.

Configurable Lift

Lift moves on a single axis configurable based on a single selection

Delivery door is self locking

Delivery door with electromechanical security lock; automatic unlocking for the withdrawl of product

Fas Cloud +

Management, programming, updates, cloning and Audit functions on site or from remote via Fas Cloud+

Typical Configurations available

Up to 3 different zone temperatures (Snack/Drink/Food); Lateral air flow to avoid build up condensation (patented)

CO2 Cooling unit monobloc

Refrigeration unit charged with CO2 (GWP=1) with inverter board to control to speed; Fast extraction due to the Slide in - Slide out system (patented)



Efficiency energy rating

TECHNICAL FEATURES

Dimensions and finishing	
Number of trays standard/maximum	6/7
Number of selections	Up to 70
Hieght - Width - Depth	1830 - 1060 - 790 mm
Footprint with door open	1810mm
Weight	350 Kg
Lift capacity	Up to 2 Kg
Aesthetic finishing	Graphite grey and black
(4) Electrical data	

Power supply	230/50-60 V/Hz
Rated power	450 W
Minimal internal temperature	3°C with health control

Amenities

Protocols	Executive/MDB
Digital Display Trays	Yes
Anti-theft bars	Optional
Easy Click system	Yes
Photocells product delivery	Yes
Pre-cooling compartment	Yes
WI-FI and bluetooth LE native	Yes

